Datasheet

DIGITUS Socket strip with aluminum profile, 12-way, 2 m cable safety plug

DN-95426
EAN 4016032483472

1U Aluminum PDU, rackmountable, 12 x C13 16A, 230VAC, 50/60Hz, Safety plug

The DIGITUS® socket strips are the perfect solution for your network or server cabinet. With regard to current distribution, the PDU fulfills the requirements of many applications in IT, network technology, laboratories and also home use. The socket strip can be compactly mounted in the cabinet in the 19" area of 1U.

Safe and professional current supply in the 482.6 mm (19”) range

- Horizontal 19" installation in the rack
- Housing: Aluminum profile
- Plastic components made of ABS UL-94V-0
- Input: Plug grounding contact CEE 7/7, 230 Vac / 16 A
- Output: Device socket 12 x IEC60320 C13, max. 10 A per output
- Cable: Cable cross section: 1.5 mm², length: 2 m
- Dimensions: 482.6 mm (19") x 45 (1U) x 45 mm (HxWxD)
- Current: 16 A
- Input Plug: CEE7/7
- Installation: Rack 1U
- Outlets: IEC 60320 C13
- Phase: 1ph
- Power: 3,6 kVA
- Volts: 230 V
- Inch form factor (IEC 60297): 482.6 mm (19")

Package contents

- Scope of delivery: 1 socket strip, 2 mounting brackets; 1 safety instructions

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	1.00	29.50	19.50	52.00	29,913.00
Packaging Unit Inside	1	0.10	5.80	9.70	51.00	2,869.26
Packaging Unit Single	1	0.10	0.00	0.00	0.00	0.00
Net single without Packaging	1	0.85	60.00	45.00	48.30	0.00

More images:








DIGITUS
DN-95426 // Socket Strip with Aluminum Profile, 12-way, 2 m Cable Safety Plug
Anschlüsse
Connections
Safety Plug
12x C13
Aluminiumprofil
Aluminium profile
Winkelprofil für die Schrankmontage
Angle profile for cabinet mounting

DIGITUS
DN-95426 // Socket Strip with Aluminum Profile, 12-way, 2 m Cable Safety Plug
Anwendungsbeispiel
Example of use
Network or Server Cabinet


DIGITUS
230 V / 10 A
Socket Strip with Aluminum Profile,
12-way, 2 m Cable Safety Plug