







- Bright Full HD 1080p projector 3800 lumens for big screen presentations
- 4K UHD and HDR compatible See more detail and texture for a greater sense of depth
- Easy connectivity 2x HDMI, USB power and built-in speaker
- Portable and lightweight Easy installation or conveniently take on the move



The EH339 is a compact Full HD projector boasting a high brightness of 3800 lumens. Designed for use any time of day, this versatile projector is suited to professional use - from meeting rooms to classrooms. This feature packed projector is 4K and HDR compatible, has a built-in speaker, offers high quality projected colours and a long lamp life for a lower overall cost of ownership.

Specifications

Display/image	
Display technology	
Resolution	1080p Full HD (1920x1080)
Brightness	3,800 lumens
Contrast ratio	22,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	0.76m ~ 7.65m (29.93" ~ 301.14") diagonal
Lamp info Light source type	Large
Light source type Lamp watts	Lamp 240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
Optical	4000 (Bright), 10000 (Bynamic), 10000 (E00)
Throw ratio	1.5:1 ~ 1.66:1
Projection distance (m)	1.0.1 ~ 1.00.1 1.1m - 10m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	15.84 ~ 17.42
Native offset	116%
Connectivity	
Connections	Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
General	
General Noise level (typical)	27dB
Noise level (typical) Noise level (max)	270B 29dB
PC compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz
	SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz), 4K UHD (24/30/50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian Japanese, Norwegian, Polish, Portuguese, Romanian, Russian Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Card style
Heat dissipation	1,023BTU/hour
Speaker count	1
Watts per speaker	3W
In the box	AC power cord
	Remote control Battery
	Basic user manual
Input lag	8.40ms
Optional wireless models	WHD200, UHDCast Pro, QuickCast
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	210W
Power consumption (max)	290W
Weight and dimensions	
Dimensions (W x D x H) mm	316 x 244 x 108
Gross weight	3.9 kg
	2.88 kg







Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 19062023112452