

DIGITUS FTTX enclosure, empty for 4 x SC SX, LC DX couplers

DN-931093
EAN 4016032466529



FTTX enclosure, empty for 4x SC SX,LC DX surface and DIN-rail mount

FTTX housing for fiber splices, terminations, storage and connections in a compact protective housing

- Suitable for 4 ports: 4 x SC SX / 4 x LC DX (without flange)
- Integrated splice cassette
- Protection type: IP45
- Installation: Wall or profile rail (DIN rail)

- Suitable for single-mode and multi-mode fiber optic cables
- Operating temperature: -40°C ~ +85°C
- Housing material: PC + ABS
- Dimensions: 100 x 80 x 30 mm (LxWxH)
- Weight: 0.4 kg
- Color: Gray

Package contents

- FTTX Housing for 4 x SC SX / LC DX Couplings

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	100	10.50	49.00	23.50	41.00	47,211.50
Packaging Unit Inside	1	0.11	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.11	9.30	10.50	3.80	371.07
Net single without Packaging	1	0.09	9.30	10.50	3.80	371.07

More images:



