FUJITSU

Data Sheet Fujitsu Display L22T-7 LED

All-round display: 54.6 cm (21.5-inch) widescreen Ease of use

The Fujitsu Display L22T-7 LED comes in a 16:9 format with a trendy style. There is no compromise in picture quality and energy efficiency. It is the best choice to get Full HD resolution with reduced office desk space. It is easy-to-use and once it is installed you never have to adjust it again - proven Fujitsu quality.

Environment-friendly LED technology

 $1920 \ x \ 1080 \ high resolution$ for pin sharp pictures with modern 16:9 format applications

Proven eco-friendliness with ENERGY STAR® 6.0

Ease of use display for home and office, high pixel density application

Due to integrated speaker no further accessories needed













Technical details

Special features

LED backlight panel, Keep aspect ratio option Stand details Stand removable Picture height over desk (min) 81 mm -3°/+20° Tilt angle Picture performance Panel and backlit TN/LED Screen Surface Treatment Anti-glare, 3H hard coating Contrast - typical 1.000:1 Contrast - advanced 20,000,000:1 Response time typical 5 ms Viewing angle (h/v) - typical 176°/170° CR5:1 Color performance 16.7 million colors (Hi-FRC) Brightness - typical 250 cd/m² Size and resolution Aspect ratio 16:9 54.6 cm (21.5-inch) **Diagonal Size** Resolution (native) 1920 x 1080 pixel (recommended) 1680 x 1050 pixel, 1600 x 1200 pixel, 1440 x 900 pixel, 1360 x 768 pixel, 1280 x 1024 pixel, 1152 x 870 pixel, 1024 **Resolution (interpolated)** x 768 pixel, 800 x 600 pixel, 720 x 400 pixel, 640 x 480 pixel Video modes 1080i/p, 720i/p, 576i/p, 480i/p Picture size 476.6 mm x 268.1 mm **Pixel Pitch** 0.248 mm Frequencies Horizontal 31 kHz to 83 kHz Horizontal analog 180 Mhz Horizontal digital 165 Mhz Vertical 55 - 76 Hz Connectivity DVI 1 x DVI (HDCP) VGA/D-SUB 1 x D-SUB Audio signal output 3.5 mm stereo phone jack Audio signal input 3.5 mm stereo phone jack Audio sound output 2 x 1.5 W OSD Languages and setting options Languages English, French, German, Italian, Polish, Spanish, Dutch, Russian, Japanese, Chinese simply Brightness / Contrast Brightness, Contrast СоІог 6500K, 7500K, 9300K, Custom Color Image adjust H-Position, V-Position, Clock, Phase, Sharpness Audio Mute, Volume Information Resolution, V-freq Input select, Language, OSD-Timeout, Factory recall Setup Power consumption (typical, w/o sound) Soft switch off 0.11 W Power save mode 0.14 W Operating with EPA settings 16.2 W Operating maximum brightness 21 W Power supply display integrated Power notes without sound

| The states have been | |
|---|---|
| Electrical values | 1001/ 2/01/ |
| Rated voltage range | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz |
| Protection class | 1 |
| Compliance | |
| Europe | CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Declaration |
| Model | W2112 |
| Russia | EAC |
| USA/Canada | FCC Class B, cUL |
| Saudi Arabia | SASO |
| Global | TCO Displays 6.0, ENERGY STAR® 6.0, EPEAT® Silver (dedicated regions), ISO9241-307 (Pixel fault class II) |
| Compliance link | http://globalsp.ts.fujitsu.com/sites/certificates |
| Quality and Reliability | |
| MTBF (demonstrated) | 60.000 h |
| Dimensions / Weight / Environmental | |
| Dimension without stand $(W \times D \times H)$ | 514.7 x 54.6 x 322.1 mm |
| | 20.26 x 2.15 x 12.68 inch |
| Dimension with stand $(W \times D \times H)$ | 514.7 x 177.7 x 369.6 mm |
| | 20.26 inch x 7.0 x 14.55 inch |
| Weight (packed) | 4.5 kg |
| | 9.92 lbs |
| Weight (unpacked) | 2.9 kg |
| | 6.39 lbs |
| Weight (Monitor only) | 2.65 kg |
| | 5.84 lbs |
| Operating ambient temperature | 5 - 35 °C (41 - 95 °F) |
| Miscellaneous | |
| Miscellaneous | VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock |
| Color | Piano black |
| Package content | |
| Display delivered accessories | Power cable for wall socket (Euro-Schuko-Type CEE7) 1.5 m, D-SUB Data cable 1.5 m , Audio cable 1.5 m, Safety |
| | booklet, Warranty booklet, Quickstart flyer, Utility CD |
| Display delivered accessories notes | Data cables and audio cable detachable on display |
| Order information | |
| Order Code | S26361-K1528-V160 |
| Country specific order code | BDL:K1528V160-UK - with UK power cable, mandatory for Arabian countries |
| EAN Code | 4053026557504 |
| Warranty | |
| Standard Warranty | 3 years (depending on country) |
| Service level | Collect & Return Service (depending on country specific requirements) |
| Warranty Terms & Conditions | http://support.ts.fujitsu.com/warranty |
| Spare Parts availability | 3 years after end of product life |
| Service Weblink | http://www.fujitsu.com/fts/services/support |
| | L -) |

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu Display L22T-7 LED, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Display L22T-7 LED, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://www.fujitsu.com/fts/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/ terms

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions Website: www.fujitsu.com/fts 2014-01-15 CE-EN All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms Copyright © Fujitsu Technology Solutions