


Technical Specifications

HP E24i G4 WUXGA Monitor




1. OSD Buttons

Front

2. Power Button

Technical Specifications

HP E24i G4 WUXGA Monitor



1. Power Button
2. DisplayPort™
3. HDMI Port
4. VGA Port

Back

5. USB-B Port
6. USB-A Ports (2)
7. USB-A Ports (2)

Technical Specifications

Models: 6PA50A8/6PA56AA

Panel Specifications	Display Size (Diagonal)	24-in
	Display Panel Type	IPS
	Micro-Edge Bezel	Yes, 3-sided
	Native Resolution/Timing	1920 x 1200 @60Hz
	Panel Bit Depth	8-bit (16.7million color)
	Aspect Ratio	16:10
	Brightness - Typical	250 cd/m ²
	Static Contrast Ratio - Typical	1000:1
	Static Contrast Ratio - Minimum	700:1
	Dynamic Contrast Ratio (DCR)	5M:1
	Flicker Free	Yes
	Pixel Pitch	0.2745 (H) x 0.2745(V)
	Pixels Per Inch (PPI)	94
	Backlight Lamp Life (to half brightness - in hours)	30k minimum
	Anti-Glare Panel	Yes (Haze 25%)
	Response Time - Typical	5ms
	Horizontal Viewing Angle (typical CR>10)	178°
	Vertical Viewing Angle (typical CR>10)	178°
	Panel Active Area (w x h)	527.04(H) x 296.46(V) mm
	Preset Graphic Modes/Supported Resolutions	640 x 480 @60Hz 720 x 400 @70Hz 800 x 600 @60Hz 1024 x 768 @60Hz 1280 x 720 @60Hz 1280 x 800 @60 HZ 1280 x 1024@60Hz 1440 x 900 @60Hz 1600 x 900 @60Hz 1680 x 1050 @60Hz
	Maximum Resolution	1920 x 1200 @60Hz
	Recommended Resolution	1920 x 1200 @60Hz
	Vertical Scan Range	50-60Hz
Horizontal Scan Range	30-80kHz	
Default Color Temperature	Neutral (6500K)	

NOTE: Performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Color Gamut Coverage	NTSC	≥CIE1931 NTSC 72% & ≥CIE1976 NTSC 83%
Color Management	Factory Color Presets	Neutral
	Color Space / Subsampling Support	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2
	Default Color Temperature	Neutral (6500 K)
	Low Blue Light Modes	Yes
	RGB Channel Adjust	No
Monitor Specifications	Exterior Color of Monitor Bezel and Stand	Black
	Plug & Play	Yes

Technical Specifications

	Tilt	-5° to +23°
	Swivel	+/-45°
	Pivot	+/-90°
	Height Adjustment Range	150mm
	VESA Mounting	Yes, 100 mm with integrated mount or with included bracket
	Security Lock Ready	Yes
	Detachable Base	Yes, ships detached
	Warranty	3-3-0 US/JP/AP/EU 3-3-3 AP/PRC
On Screen Display (OSD)	On Screen Display User Controls	Brightness+, Color, Image, Input, Power, Menu, Management, Information (Power delivery up to 15W)
	Monitor Control Buttons or Switches	Menu, Minus ("-")/Information, Plus ("+") /Viewing Mode, OK/Next Active Input, Power
	User-Assignable Function Buttons	Yes, 3 (6 Options)
	Languages	10 (German, Dutch, T-Chinese and S-Chinese, English, Spanish, French, Italian, Japanese, Portuguese)
Connector Types	DisplayPort™	1 DisplayPort™ 1.2 in
	HDMI	1 HDMI1.4
	VGA	1
	HDCP support	Yes
USB Port Specifications	USB Version	3.2
	USB Hub	Yes
	Downstream Ports	4 Ports
	Upstream Ports	1 Port
	Fast Charging USB Ports	1 Port (Side) (USB-A)
	Power Output Maximum	Fast Charging: 7.5 W
Special Features	User Presets	Yes
	User Updateable Firmware	Yes
Power & Operating Specs	Power Supply	Internal
	Power Source	100 – 240 VAC 50/60 Hz
	Power Consumption - Maximum	35 W
	Energy Saving/Standby Mode	0.5 W
	Power Consumption - Typical	36 W
	Power cable length	1.9 m
EU Energy Efficiency Class (EC1062)	On-mode Power Consumption (EC 1062/2010)	16 W
	Annual Power Consumption (EC 1062/2010)	24 kWh
	Energy Efficiency Class (EC 1062/2010)	A+
	Visible Screen Size	24" / 60.69 cm Diagonal
Operating Conditions	Operating Temperature - Celsius	5°– 35°C
	Operating Temperature - Fahrenheit	41°C – 95°F
	Non-operating Temperature - Celsius	-34° – 60°C
	Non-operating Temperature - Fahrenheit	-29° – 140°F
	Operating Humidity	20 – 80% Relative Humidity (non-condensing)

Technical Specifications

	Non-operating Humidity	5 – 95%
	Operating Altitude	0 – 5,000 m (16,400 ft.)
	Non-operating Altitude	0 – 12,192 m (40,000 ft.)
Environmental Features and Certifications	Mercury-free LED display backlighting	Yes, Mercury-free LED backlighting
	Arsenic-Free Display Glass	Yes
	Low Halogen*	Yes GSE HP-00011-01B, table 2 defines low-halogen (BFR, CFR, PVC) NOTE: External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.
	Agency Approvals and Certifications	WW certificate CE, CB, KC/KCC/NOM/ISO 9241-307/ EAC/TUV-GS/cTUVus/PSB/CCC/CEL/ISC/VCCI/FCC/BSMI/Vietnam MEPS/Australian-New Zealand MEPS/WEEE/BIS/CEC/E-Standby/Low Blue Light/CECP/TUV-S/CECP
	Microsoft WHQL Certification	Win 10, Win 8, Win 7
	China Energy Label	CEL Grade 1
	SmartWay Transport Partnership - NA only	Yes (NA SKU)

*External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

NOTE: DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

		Metric	Imperial
Unit Product/Package Specifications	Product Dimensions (Unpacked with stand) (W x D x H)	53.2 x 20.69 x 50.96 cm	20.94 x 8.15 x 20.06 in
	Product Dimensions (Packed) (W x D x H)	60.5 x 42 x 22.4 cm	23.82 x 16.54 x 8.82 in
	Display Head Dimensions (Unpacked without stand) (W x D x H)	53.2 x 4.7 x 35.27 cm	20.94 x 1.85 x 13.88 in
	Base Area Footprint (w x d mm)	260 x 207 mm	10.23 x 8.15 in
	Bezel Measurements	Bottom 20.73 mm (display chin)	Bottom 8.16 in (display chin)
		Product Weight (Unpacked with stand)	6.06 kg
	Product Weight (Packed)	9.12 kg	20.1 lb
	Product Weight (Head Only)	3.6 kg	7.94 lb
Pallet Information	Pallet Dimensions (L x W x H)	1220 x 1140 x 2243 mm	48.03 x 44.88 x 88.31 in
	Pallet Total Weight (L x W x H)	40" GQ: 384 kg 40" HQ: 476 kg	40" GQ: 847 lbs 40" HQ: 1050 lbs
	Pallet Layers	GQ: 4 HQ: 5	
	Pallet Product per Layer	8	
	Total Products per Pallet	GQ: 32 HQ: 40	
		Container Load, 20-Foot	460
	Container Load, 40-Foot	960	
	Container Load, 40-Foot HighQ	960	

Technical Specifications

Software Included	HP Display Assistant	
What's in the box?	1 HDMI	(1.8 m) 5.9 ft
	1 DisplayPort™ (DisplayPort™ 1.2)	(1.8 m) 5.9 ft
	1 USB-A-B cable	(1.8 m) 5.9 ft
	1 Power Cord	(1.9 m) 6.2 ft
	1 QSP	
1 Doc-Kit		
User Guide and Warranty Languages	User Guide Languages	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.
	Warranty Languages	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.

Technical Specifications

Copyright © 2020 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.

Summary

Change Log

Change Log			
	V1 to V2		