


### Overview

### Models

HP HDMI to VGA Adapter	H4F02AA
HP EliteFolio Ethernet & VGA Adapter <b>New!</b>	F3W44AA
HP HDMI to DVI Adapter <b>New!</b>	F5A28AA
HP DisplayPort to HDMI 1.4 Adapter <b>New!</b>	F3W43AA

### HP HDMI to VGA Adapter (H4F02AA)



The HP HDMI to VGA Adapter allows you to convert the HDMI output port on your HP Business Notebook PC to an analog VGA input so you can connect to an external VGA display.


<b>Host Interface</b>	HDMI	
<b>Video Interface</b>	VGA	
<b>Connectors</b>	<b>Video output</b>	VGA male connector
	<b>Host upstream link</b>	HDMI male connector
<b>Supported Resolutions</b> (external display)	600 x 800 768 x 1280 1024 x 1280 1050 x 1680 1080 x 1920	
<b>Operating Temperature</b>	0-40°C (32-104° F)	
<b>Storage Temperature</b>	-10~70°C (14~158 °F)	
<b>System Requirements</b>	<b>Software</b>	Microsoft® Windows® 7 with Service Pack 1 (32-bit or 64-bit), Windows Vista® with Service Pack 1 (32-bit or 64-bit), Microsoft® Windows® XP Home or Professional with Service Pack 3
<b>Mechanical</b>	<b>Dimensions (H x W x L)</b>	<b>Unpackaged:</b> 0.59 x 1.574 x 1.771 in (15 x 40 x 45 mm)
	<b>Weight</b>	<b>Unpackaged:</b> 1.093 oz (31 g)
<b>Environmental</b>	<b>EMC</b>	FCC Part 15 Class B, IC ICES-003, CE (EN55022, EN61000, EN55024), BSMI, UL, C-tick, VCCI, KC
	<b>RoHS</b>	RoHS Compliant
<b>Dimensions</b>	6.22 x 1.57 x 0.59 in 150.8 x 40 x 15 mm	
<b>Weight Unpackaged</b>	0.088 lb (40 g)	
<b>Components</b>	HP HDMI to VGA Adapter, Warranty Card, and Quick Installation Guide	
<b>Compatibility</b>	<ul style="list-style-type: none"> <li>● HP Folio<sup>13</sup></li> <li>● HP Envy 4</li> <li>●</li> <li>●</li> </ul>	



### Overview

- HP SpectreXT
- HP ProBook 4230s, 4330s, 4340s, 4341s, 4430s, 4431s, 4435s, 4436s, 4440s, 4441s, 4446s, 4530s, 4540s, 4535s, 4545s, 4730s, and 4740s Notebook PCs
- HP 430, 431, 435, 436, 450, 455, 630, 631, 635, 636, 650, and 655 Notebook PCs
- HP ProBook 5330m Notebook PC

### HP EliteFolio Ethernet & VGA Adapter (F3W44AA)




Expand what you can do with your HP EliteBook Folio 1040 G1 by using its side dock connector to add Ethernet and VGA connectivity with a single handy adapter.

- Connect the adapter to the notebook's side docking port to quickly add RJ-45 and VGA ports.
- Store the compact adapter in your carrying case alongside your notebook.
- Get a one-year parts replacement limited warranty.

<b>Environmental Data</b>	<b>Operating Temperature</b> -25° to +85° 85%RH, without loss of function. Storage temperature: -25° to +70° 85%RH, without loss of function.
<b>RJ45 Durability</b>	The test is performed in accordance with EIA-364-09C.Total:2000 cycles. The speed is 500 cycles per hour.
<b>VGA Durability</b>	The test is performed in accordance with EIA-364-09C.Total:1000 cycles. The speed is 500 cycles per hour.
<b>Test Condition</b>	<b>Temperature:</b> 15° to 35° <b>Relative Humidity:</b> 40% to 70% <b>Atmospheric pressure:</b> 650 to 800 millimeters (25.6 to 31.5 inches) of Mercury.
<b>Dimensions</b>	5.91 x 2.36 x 0.59 in 150 x 60 x 15 mm
<b>Weight Unpackaged</b>	0.081 lb (37 g)
<b>Compatibility</b>	<ul style="list-style-type: none"><li>• HP EliteBook Folio 1040 G1</li></ul>

### HP HDMI to DVI Adapter (F5A28AA)

### Overview



- Maximize your HP Business Notebook's available ports with the HP HDMI to DVI Adapter. Convert your HDMI output to DVI for quick and easy connection to an external display.

### Features

- Input : HDMI, support HDMI up to ver 1.4a
- Output : DVI-D with 24+1 pins connector

**Operating Systems Supported** Support Windows: Windows 7 & 8;  
Use system default driver

**Power Source** Standard HDMI

**Temperature & Humidity** **Operating**  
The HDMI to DVI connector adapter shall perform to specification when exposed to ambient temperatures of 410F to 950F( 50C to 350C), 8%~ 80% RH (non-condensing).

**Storage**  
The HDMI to DVI connector adapter shall be able to withstand prolonged exposure to temperatures from 410F to 1040F( 50C to 400C), 8%~ 80% RH (non-condensing) encountered during transportation or storage.

**Environmental Requirements** To meet WEEE/RoHS and HALOGEN FREE requirements, all materials must meet limits contained within the HP standard 011-0 general specification for the environment (GSE), A-5951-1745-1. The test method accepted only is IEC62321.

**Dimensions (LxWxH)** 2.29 x 1.61 x .59 in  
58.25 x 41 x 15 mm


**Weight Unpackaged** .05 lb (23 g)

**Compatibility**

- HP ProBook 430 G1, 440 G0, 450 G0, 470 G0, 440 G1,
- HP ProBook 4441s, 4446s, 4340s, 4341s, 4540s, 4545s, 4740s, 4230s, 4430s, 4431s, 4330s, 4436s, 4435s, 4530s, 4535s, 4730s, 4441s,
- HP SpectreXT Pro
- HP ChromeBook 14
- HP Spectre 13 Pro
- HP Spectre x2
- HP 215 Notebook PC
- HP ProBook 3125
- HP 240 G2, 245 G2, 250 G2, 255 G2, 455

### Overview

### HP DisplayPort to HDMI 1.4 Adapter (F3W43AA)



Make the most of the available ports on your HP Business Notebook by converting its DisplayPort output to HDMI for quick and easy connection to a range of multimedia devices.

#### Product Features

- Compliant to HDMI 1.4a specification up to 3.0Gbps
- Support 4K x 2K & 3D video formats over HDMI
- Support DisplayPort all 4 levels of output and all 4 levels of pre-emphasis

#### Highest Video

**Resolution** 1920x1200 1600x1200

#### Resolution Supported

**Refreshing Rate** 60Hz

**Reduced Blanking** RB

**Pixel Frequency** 154MHz 162MHz

**NOTE:** All video timings within four lane DisplayPort bandwidth are supported

#### Normal operating conditions

**Parameter** **Ambient Temperature** Min 0 C Max 40 C

**HDMI source level shifter** **Type** 220 **Max** 300 **Unit** mA

#### Electronics Character SPEC

**Input Voltage** 3.3V ± 10% 3.3V 230mA

**Output** 5V ± 10% Max 90mA

**Power consumption** 760mW Max

**Power down current** 8mA Max

**EMI** Standard Limit line FCC Part15 Class B

**ESD** AIR ± 4KV IEC61000-4-2

Contact ± 2KV

**Compliance** DisplayPort 1.1a / DVI 1.0

**Dimensions (LxWxH)** 1.98 x 0.94 x 0.50 in  
50.28 x 24.00 x 12.80 mm

**Weight Unpackaged** 0.030 lb (13.5 g)

#### Compatibility

- HP ProBook 640 G1, 645 G1, 650 G1, 655 G1
- HP ProBook 6470b, 6475b, 6570b
- HP EliteBook 820 G1, 840 G1, 850 G1
- HP ZBook 14, 15, 17
- HP Elitebook 2170p, 2570p, 8470p,8570p, 8470w, 8570w,8770w

### Overview

#### **Service and support**

Each accessory carries a one-year limited warranty. Technical support is available seven days a week, 24 hours a day, by phone, as well as online support forums. Certain restrictions and exclusions apply.

---

Copyright © 2014 Hewlett-Packard Development Company, L.P. All rights reserved.

The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. All other trademarks are the property of their respective owners.