

DX-55



A concise appearance of dual-sided display featuring 55" high brightness panels and movable floating frame, is designed specifically for diverse professional digital signage applications.

With Full HD resolution, 700 nits of brightness and a 3000:1 contrast ratio, DX-55 is able to provide the impressive image performance in diverse settings. Dual HDMI connections and ample space make it easy for IPC or media player integration. With unique floating frame design and metal housing, DX-55 provides another premium choice for retail, point of sale, and advertising markets in public environments.

- > 55" dual-sided LCD signage
- > Glass protected floating frame
- > MVA panel for wide viewing angle
- > FHD 1920 x 1080 resolution
- > 700 nits of brightness fulfills diverse surrounding requirements
- > 3000:1 contrast ratio
- > Dual HDMI connections for connecting media players/ IPC
- > Separately driven display contents on each screen
- > Free standing and movable floor stand on removable casters
- > Durable metal housing
- > Optional flight case (FTC-55E)



700 nits



Mobility



IPC
flexibility



Content
separateness

DX-55

Specifications

DX-55

Panel	Panel Type	LED-Backlit TFT LCD (MVA Panel)
	Panel Size	55"
	Max. Resolution	1920 x 1080 (FHD)
	Pixel Pitch (H x W)	0.63 x 0.63 mm
	Brightness	700 nits
	Contrast Ratio	3000:1
	Viewing Angle	178
	Viewable Size (H x V)	1209.6 x 680.4 mm
	Display Colour	10.7B
	Response Time (GTG)	6.5 ms
	Colour Gamut	72 (%)
Surface Treatment	Haze 11%, 3H	
Input	HDMI	HDMI x 2 (With HDCP)
Power	Power Supply	AC 110 ~ 240V, 50/60Hz
	Power Consumption	230 W (Typical)
	Light source	LED
Operating Conditions	Temperature	0°C ~ 40°C (32°F~104°F)
	Humidity	20%~80% (No condensation)
Storage Conditions	Temperature	-10°C ~ 50°C (14°F~122°F)
	Humidity	20%~80% (No condensation)
Dimensions	Display (H x W x D)	2021.5 x 1011.6 x 458.4 mm (79.6 x 39.8 x 18.0 in)
	Packing (H x W x D)	2207 x 1184 x 666 mm (86.9 x 46.6 x 26.2 in)
Weight	Net	140 kg (308.4 lb)
	Gross	150 kg (330.7 lb)
Regulation Approval	Certifications & Compliance	CB, CE, RoHS, WEEE, REACH
Accessories	Supplied	Power cable 110~240V x1 IPC
	Optional	Flight case (FTC-55E) (L) 1084 x (W) 520 x (H) 2090 mm



Concise floating frame design



Free standing and movable floor stand on removable casters



HDMI connections and ample space for media player/IPC integration



Durable metal housing

